

TERMINAL PITCH	2.5MM				3.5MM							3.81MM				5.0MM										
Part no.	CTBP2054	CSTBP92HC	CTBP93VC	CTBP93HC	CTBP3051	CTBP0305	CTBP0355	CTBP92HD	CTBP92VD/S	CTBP92VD/R	CTBP93HD	CTBP93VD	CSTBP92HD	CTBP0308	CTBP92HE	CTBP92VE/S	CTBP92VE/R	CTBP93HE	CTBP93VE	CSTBP92HE	CTBP5000	CTBP5050	CTBP0500	CTBP1000	CTBP1050	CTBP0100
Page no.	12	76	76	76	13	14	15	58	58	58	59	59	77	16	60	60	60	61	61	78	17	18	19	21	22	23
STYLE OF BLOCK	2.5MM				3.5MM							3.81MM				5.0MM										
Low profile	•				•	•	•														•	•	•			
Standard profile		•	•	•				•	•	•	•	•	•	•	•	•	•	•	•	•				•	•	•
High power																										
Pluggable female		•						•	•	•			•	•	•	•				•						
Pluggable male			•	•							•	•						•	•							
Pin header																										
Screwless pluggable		•											•								•					
Screw flanges																										
Inverted pluggable																										
Cut-to-size																										
Interlocking					•	•	•							•								•	•	•	•	•
Solid block	•	•	•					•	•	•	•	•	•	•	•	•	•	•	•	•	•					
ORIENTATION	2.5MM				3.5MM							3.81MM				5.0MM										
Vertical - side entry	•				•	•			•	•				•	•	•					•	•	•		•	•
Vertical - top entry		•	•								•	•					•	•								
Horizontal (90°) - side entry				•			•				•						•									
Horizontal (90°) - top entry								•						•								•			•	
45° Angle																										
RATING (NOMINAL)	2.5MM				3.5MM							3.81MM				5.0MM										
4A		•	•																							
6A	•																									
8A								•	•	•	•	•	•	•	•	•	•	•	•	•						•
10A					•		•																			
15A							•							•												
16A																					•	•		•	•	•
20A																										
22A																										
30A																										
52A																										
CABLE ACCEPTANCE	2.5MM				3.5MM							3.81MM				5.0MM										
30-12 AWG (0.2-2mm)																										
28-16 AWG (0.32-1.3mm)							•	•	•	•			•	•	•	•	•			•						
28-14 AWG (0.32-1.6mm)																										
26-20 AWG (0.4-0.8mm)		•																								
26-18 AWG (0.4-1mm)		•																								
26-16 AWG (0.4-1.3mm)																										
26-12 AWG (0.4-2mm)																										
26-10 AWG (0.4-2.6mm)																										
24-18 AWG (0.5-1mm)							•	•																		
24-12 AWG (0.5-2mm)																										
22-16 AWG (0.6-1.3mm)																										•
22-14 AWG (0.6-1.6mm)																						•	•		•	•
22-12 AWG (0.6-2mm)																										•
22-6 AWG (0.6-4.1mm)																										
TERMINAL TYPE	2.5MM				3.5MM							3.81MM				5.0MM										
Wire protector							•	•													•	•		•	•	
Rising clamp	•						•	•	•	•				•	•	•	•						•			•
Spring cage		•											•								•					

TERMINAL PITCH	5.0MM														5.08MM																
Part no.	CTBP0150	CTBP0550	CTBP0700	CTBP0750	CTBP7000	CTBP3000	CTBP90HG	CTBP90VG	CTBP9200	CTBP92VG/S	CTBP92VGR	CTBP9300	CTBP9350	CTBP9300 AO	CTBP9350 AO	CTBP9200 FL	CTBP9300 FL	CTBP9350 FL	CTBP1301	CTBP1301/PS	CTBP0108	CTBP0158	CTBP0508	CTBP0558	CTBP0708	CTBP0758	CTBP9208	CTBP3008	CTBP92VJ/S	CTBP92VJ/R	
Page no.	22	20	28	29	25	26	27	27	62	62	62	63	63	63	63	64	64	64	74	74	32	33	30	31	35	36	65	34	65	65	
STYLE OF BLOCK	5.0MM														5.08MM																
Low profile																															
Standard profile																															
High power																															
Pluggable female																															
Pluggable male																															
Pin header																															
Screwless pluggable																															
Screw flanges																															
Inverted pluggable																															
Cut-to-size																															
Interlocking																															
Solid block																															
ORIENTATION	5.0MM														5.08MM																
Vertical - side entry																															
Vertical - top entry																															
Horizontal (90°) - side entry																															
Horizontal (90°) - top entry																															
45° Angle																															
RATING (NOMINAL)	5.0MM														5.08MM																
4A																															
6A																															
8A																															
10A																															
15A																															
16A																															
20A																															
22A																															
30A																															
52A																															
CABLE ACCEPTANCE	5.0MM														5.08MM																
30-12 AWG (0.2-2mm)																															
28-16 AWG (0.32-1.3mm)																															
28-14 AWG (0.32-1.6mm)																															
26-20 AWG (0.4-0.8mm)																															
26-18 AWG (0.4-1mm)																															
26-16 AWG (0.4-1.3mm)																															
26-12 AWG (0.4-2mm)																															
26-10 AWG (0.4-2.6mm)																															
24-18 AWG (0.5-1mm)																															
24-12 AWG (0.5-2mm)																															
22-16 AWG (0.6-1.3mm)																															
22-14 AWG (0.6-1.6mm)																															
22-12 AWG (0.6-2mm)																															
22-6 AWG (0.6-4.1mm)																															
TERMINAL TYPE	5.0MM														5.08MM																
Wire protector																															
Rising clamp																															
Spring cage																															

TERMINAL PITCH	5.08MM														6.35MM		7.5MM							
Part no.	CTBP9308	CTBP9308/FL	CTBP9358	CTBP9358/FL	CTBP9308 AO	CTBP9358 AO	CTBP96HJ	CTBP96HJ FL	CTBP9208 FL	CTBP97VJ	CTBP97VJ FL	CTBP97HJ	CTBP97HJ FL	CSTBP9208	CTBP04VY	CTBP55VK	CTBP07VK	CTBP010	CTBP015	CTBP9400	CTBP9500	CTBP9550		
Page no.	66	67	66	67	66	66	72	72	67	72	73	73	73	79	37	38	41	39	40	68	68	68		
STYLE OF BLOCK	5.08MM														6.35MM		7.5MM							
Low profile																	•							
Standard profile	•	•	•	•	•	•	•	•	•	•	•	•	•	•				•	•	•	•	•	•	
High power															•		•							
Pluggable female									•	•	•	•	•	•							•			
Pluggable male	•	•	•	•	•	•	•	•														•	•	
Pin header																								
Screwless pluggable														•										
Screw flanges		•		•		•	•		•		•		•											
Inverted pluggable					•		•	•		•	•	•	•											
Cut-to-size																								
Interlocking															•	•	•	•	•					
Solid block	•	•	•	•	•	•	•	•	•	•	•	•	•	•								•	•	•
ORIENTATION	5.08MM														6.35MM		7.5MM							
Vertical - side entry															•	•	•	•						
Vertical - top entry	•	•			•					•	•			•								•		
Horizontal (90°) - side entry			•	•		•						•	•										•	
Horizontal (90°) - top entry							•	•	•										•	•				
45° Angle																								
RATING (NOMINAL)	5.08MM														6.35MM		7.5MM							
4A																								
6A																								
8A																								
10A														•										
15A	•	•	•	•	•	•	•	•	•	•	•	•	•	•								•	•	•
16A																•		•	•					
20A																	•							
22A																								
30A															•									
52A																								
CABLE ACCEPTANCE	5.08MM														6.35MM		7.5MM							
30-12 AWG (0.2-2mm)																								
28-16 AWG (0.32-1.3mm)																								
28-14 AWG (0.32-1.6mm)							•	•	•					•							•			
26-20 AWG (0.4-0.8mm)																								
26-18 AWG (0.4-1mm)																								
26-16 AWG (0.4-1.3mm)																								
26-12 AWG (0.4-2mm)																		•						
26-10 AWG (0.4-2.6mm)															•									
24-18 AWG (0.5-1mm)																								
24-12 AWG (0.5-2mm)																								
22-16 AWG (0.6-1.3mm)																								
22-14 AWG (0.6-1.6mm)																•								
22-12 AWG (0.6-2mm)																		•	•					
22-6 AWG (0.6-4.1mm)																								
TERMINAL TYPE	5.08MM														6.35MM		7.5MM							
Wire protector																	•							
Rising clamp					•	•	•								•		•	•	•	•				
Spring cage														•										

TERMINAL PITCH	7.5MM		7.62MM								9.5MM	10MM								10.16MM			
Part no.	CTBP9500/AO	CTBP9550/AO	CTBP9408	CTBP018	CTBP01HL	CTBP07VL	CTBP9508	CTBP9558	CTBP9508 AO	CTBP9558 AO	CTBP04VZ	CTB0602	CTBP2000	CTB0202	CTBP6550	CTBP2550	CTBP2050	CTBP6000	CTBP6050	CTBP4000	CTB0609	CTBP977VP	
Page no.	69	69	70	42	43	44	70	70	71	71	44	48	51	52	49	53	51	46	47	54	55	56	
STYLE OF BLOCK	7.5MM		7.62MM								9.5MM	10MM								10.16MM			
Low profile																							
Standard profile	•	•	•	•	•		•	•	•	•			•	•		•	•						
High power				•	•	•					•												•
Pluggable female			•																				
Pluggable male	•	•						•	•	•	•												
Pin header																							
Screwless pluggable																							
Screw flanges																							
Inverted pluggable																							
Cut-to-size																							
Interlocking				•	•	•					•	•	•	•	•	•	•	•	•	•	•	•	•
Solid block	•	•	•					•	•	•	•									•	•		
ORIENTATION	7.5MM		7.62MM								9.5MM	10MM								10.16MM			
Vertical - side entry				•		•					•	•	•					•				•	•
Vertical - top entry	•							•		•													
Horizontal (90°) - side entry		•							•		•												
Horizontal (90°) - top entry			•		•										•	•	•		•				
45° Angle																						•	
RATING (NOMINAL)	7.5MM		7.62MM								9.5MM	10MM								10.16MM			
4A																							
6A																							
8A																							
10A												•		•									•
15A	•	•	•					•	•	•	•											•	
16A													•		•	•	•	•	•	•			
20A				•	•	•																	
22A																							
30A											•												
52A																							•
CABLE ACCEPTANCE	7.5MM		7.62MM								9.5MM	10MM								10.16MM			
30-12 AWG (0.2-2mm)				•																			
28-16 AWG (0.32-1.3mm)																							
28-14 AWG (0.32-1.6mm)				•																			•
26-20 AWG (0.4-0.8mm)																							
26-18 AWG (0.4-1mm)																							
26-16 AWG (0.4-1.3mm)													•	•									•
26-12 AWG (0.4-2mm)						•	•																
26-10 AWG (0.4-2.6mm)											•												
24-18 AWG (0.5-1mm)																							
24-12 AWG (0.5-2mm)																							
22-16 AWG (0.6-1.3mm)															•								
22-14 AWG (0.6-1.6mm)																	•	•	•				
22-12 AWG (0.6-2mm)															•		•						
22-6 AWG (0.6-4.1mm)																							•
TERMINAL TYPE	7.5MM		7.62MM								9.5MM	10MM								10.16MM			
Wire protector													•				•	•	•				
Rising clamp			•	•	•	•					•	•		•	•	•					•	•	•
Spring cage																							